



## Descriptions

- \* With mp3/TUNER/Bluetooth functions.
- \* Apply in small places which need Public address system

## Features

- \* Standard machine cabinet design (1U), contraption, Exquisite craft, high-grade temperament.
- \* With mp3/TUNER/Bluetooth module, Digital screen displaying the current music from USB.
- \* With mp3/TUNER/Bluetooth remote control function.
- \* 1 EMC input, 2 AUX input, 4 MIC input.
- \* Channel priority: EMC>MIC1>MIC2, MIC3, AUX1, AUX2.
- \* Each channel has volume control function, master volume controls and bass/treble tone control.
- \* Has level indicator, overload and protection indicator.
- \* With High temp, overload & short-circuit protection.
- \* 2 output modes: 100V, 70V (non- Bridged mode).
- \* High energy and energy saving design of power supply and efficient power amplifier.

## Specifications

Model	T-60TB
output terminal	70V, 100V
Output Power	60W
The input sensitivity and impedance	MIC1, 2, 3, 4 input:5mV/600 $\Omega$ Unbalanced 6.3 connector AUX1, 2 input:350mV/10K $\Omega$ Unbalanced RCA connector EMC input:775mV/10K $\Omega$ Unbalanced 6.3 connector
The output sensitivity & source impedance	MIX OUT:1000mV/470 $\Omega$ Unbalanced RCA connector
Tone	Bass: $\pm 10$ dB at 100Hz Treble: $\pm 10$ dB at 10KHz
Frequency Response	50Hz~16KHz (+1dB, -3dB)
SNR	MIC1, 2, 3:66dB; AUX1, 2:80dB
THD	Less than 0.5%( at 1KHz, 1/3 rated power)
Mute Control	MIC 1 has highest priority and EMC has the second
Crosstalk	$\geq 50$ dB
Heat dissipation	Cooling fan starts when amplifier turned on, infinitely variable speeds
Protection	Over-heat, overload, short, etc
Power Supply	$\sim 220$ V /50Hz
Power consumption	100W
Size	484 x 260 x 44mm
Weight	4.1Kg